



**US Army Corps
of Engineers.**

Engineer Research and
Development Center

ERDC/CHL TR-00-2

Coastal and Hydraulics Laboratory

Barbers Point Harbor Physical Model Navigation Study

Gordon S. Harkins, Cecil C. Dorrell

March 2000

20000530 036

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.



PRINTED ON RECYCLED PAPER

ERDC/CHL TR-00-2
March 2000

Barbers Point Harbor Physical Model Navigation Study

by Gordon S. Harkins, Cecil C. Dorrell

U.S. Army Engineer Research and Development Center
Waterways Experiment Station
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Final report

Approved for public release; distribution is unlimited

Prepared for U.S. Army Engineer Division, Pacific Ocean
Fort Shafter, HI 96858-5440

Engineer Research and Development Center Cataloging-in-Publication Data

Harkins, Gordon S.

Barbers Point Harbor physical model navigation study / by Gordon S. Harkins, Cecil C. Dorrell ; prepared for U.S. Army Engineer Division, Pacific Ocean.

157 p. : ill. ; 28 cm. — (ERDC/CHL ; TR-00-2)

Includes bibliographic references.

1. Barbers Point Harbor (Hawaii) — Mathematical models. 2. Barbers Point Harbor (Hawaii) — Navigation. 3. Harbors — Hawaii — Hydrodynamics. I. Dorrell, Cecil C. II. United States. Army. Corps of Engineers. Pacific Ocean Division. III. Engineer Research and Development Center (U.S.) IV. Coastal and Hydraulics Laboratory (U.S.) V. Title. VI. Series: ERDC/CHL TR ; 00-2.

TA7 E8 no.ERDC/CHL TR-00-2

Table F7.	Number of Occurrences of Keel Motion Through Different Depth Bins for Modified Bunga Saga Empat, 42-ft Vessel Draft, 47-ft Entrance-Channel Depth, Waves 0-deg Orientation to Entrance Channel, Run 7 in Entrance Channel	F8
Table F8.	Number of Occurrences of Keel Motion Through Different Depth Bins for Modified Bunga Saga Empat, 42-ft Vessel Draft, 47-ft Entrance-Channel Depth, Waves 0-deg Orientation to Entrance Channel, Run 8 in Entrance Channel	F9
Table G1.	Mean and Maximum H_s , Based on Numerical Modeling	G7
Table G2.	Percent Occurrence of H_s Greater than 0.3 m (1 ft), Based on Numerical Modeling	G7
Table G3.	Average Barge Basin H_s Response to Storms, Based on Physical Model Experiments	G9
Table G4.	Physical Model Cases with Lowest and Highest Barge Basin Response	G10
Table H1.	Barbers Point Harbor Plans 7a and 7b	H1
Table H2.	Parameter Values Used in HARBD	H2
Table H3.	Grid Size	H2

5 knots were used for experiments around the transition as well as in the entrance channel.

